

Custos

Increasing Security with Secret Storage as a Service

Andy Saylor
Dirk Grunwald

TRIOS14
10/05/14



University of Colorado **Boulder**

Where do we store data today?









Trust?



Secure?





How can we control
and protect our data?

How can we control
and protect our data?


(even when storing it with third parties)


Client-Side Encryption?





But What About the Keys?






Custos


Custos

Latin for "Guard"

“Key Storage as a Service”

“Secret Storage as a Service”





Core Features

Centralized Secret Storage

Centralized Secret Storage

Flexible Access Control

Centralized Secret Storage

Flexible Access Control

Auditing and Revocation

Centralized Secret Storage


Example: Multi-Device File Sync




Example: Multi-Device File Sync




Example: Multi-Device File Sync




Example: Multi-Device File Sync




Example: Multi-Device File Sync




Example: Multi-Device File Sync




Example: Multi-Device File Sync




Example: Multi-Device File Sync




Example: Multi-Device File Sync




Example: Multi-Device File Sync



Example: Multi-Device File Sync



Example: Multi-Device File Sync



Managed SSH Agent

Managed SSH Agent
Scalable SSL Processor

Managed SSH Agent
Scalable SSL Processor
Etc...

Centralized Secret Storage in Custos

Custos Server

```
graph TD; CS[Custos Server] --- CA[Client A]; CS --- CB[Client B]; CS --- CC[Client C];
```



Custos Server


Client A

Client B


Client C











Trust?









Do you have to trust
a single provider?

Multi-Provider Sharding

Multi-Provider Sharding


Shamir Secret Sharing






Provider A

Custos
Key Store




Client
Application




Provider A

Custos
Key Store










Provider B


Custos
Key Store





Client
Application











Availability

Availability

Sharding with (k, n) Threshold Scheme

Centralized Secret Storage

Centralized Secret Storage

Flexible Access Control

Example: Autonomous Server Bootup



Example: Autonomous Server Bootup



Example: Autonomous Server Bootup



Example: Autonomous Server Bootup



Example: Autonomous Server Bootstrap



CorrectHorseBatteryStaple




Example: Autonomous Server Bootstrap




CorrectHorseBatteryStaple




Example: Autonomous Server Bootup



Example: Autonomous Server Bootup



Example: Autonomous Server Bootup




Example: Autonomous Server Bootup




Example: Autonomous Server Bootup




Example: Autonomous Server Bootstrap




Example: Autonomous Server Bootstrap




Example: Autonomous Server Bootstrap




Example: Autonomous Server Bootstrap



Example: Autonomous Server Bootup



Example: Autonomous Server Bootup




Backup Systems


Backup Systems


Time-Limited Access


Backup Systems
Time-Limited Access
Etc...

Flexible Access Control in Custos









“Secret”

“Secret”

Access Control Specification (ACS)

"Secret"

Access Control Specification (ACS)


Permission A

“Secret”

Access Control Specification (ACS)

Permission A

Access Control
Chain



“Secret”

Access Control Specification (ACS)

Permission A

Access Control Chain

Auth
Attribute



Auth
Attribute



Auth
Attribute

“Secret”

Access Control Specification (ACS)

Read Permission

Access Control
Chain

Auth
Attribute



Auth
Attribute



Auth
Attribute

"Secret"

Access Control Specification (ACS)

Read Permission

Access Control
Chain

Username



IP Address



Password

"Secret"

Access Control Specification (ACS)

Read Permission

Access Control
Chain

Username



IP Address



Password

Update Perm.

Access Control
Chain

Username



IP Address

⋮

■ ■ ■

"Secret"

Access Control Specification (ACS)

Read Permission

Access Control
Chain

Username



IP Address



Password

Access Control
Chain

Username



User Cert

⋮

...

Update Perm.

Access Control
Chain

Username



IP Address

⋮

...

■ ■ ■

Authentication Attributes

Authentication Attributes

Plugin-Based

Explicit

ip_src

user_agent

time_utc

...

Implicit

user_id

psk

psk_sha256

...

Centralized Secret Storage

Flexible Access Control

Centralized Secret Storage

Flexible Access Control

Auditing and Revocation

Example: Revoke Shared Access




Example: Revoke Shared Access




Example: Revoke Shared Access




Example: Revoke Shared Access




Example: Revoke Shared Access




Example: Revoke Shared Access




Example: Revoke Shared Access




Example: Revoke Shared Access




Example: Revoke Shared Access



Example: Revoke Shared Access




Example: Revoke Shared Access




- 140813: Bob Accessed 
- 140906: Bob Accessed 
- 141003: Bob Accessed 

Example: Revoke Shared Access




140813: Bob Accessed 
140906: Bob Accessed 
141003: Bob Accessed 


Example: Revoke Shared Access



140813: Bob Accessed 
140906: Bob Accessed 
141003: Bob Accessed 


Auditing and Revocation in Custos






140813: Bob Accessed Key A
140906: Bob Accessed Key B
141003: Bob Accessed Key A

140813: Bob Accessed Key A
140906: Bob Accessed Key B
141003: Bob Accessed Key A



Revocation
Semantics


140813: Bob Accessed Key A
140906: Bob Accessed Key B
141003: Bob Accessed Key A



Revocation
Semantics

Intrusion
Detection

140813: Bob Accessed Key A
140906: Bob Accessed Key B
141003: Bob Accessed Key A



Revocation
Semantics


Intrusion
Detection



Compliance
Verification


Custos Prototype


Custos Prototype


EncFS: Custos-Backed Encrypted File System













(a) dd Copy Throughput (MB/s)



(b) ioping Write Latency (ms)



(c) bonnie++ Create IOPS

Current and Future Work

Additional Client Applications

(SSH Key Manager, PKCS11 SSL Processor, Etc)

Additional Client Applications
(SSH Key Manager, PKCS11 SSL Processor, Etc)

Better Management of Secret Sharing

Additional Client Applications
(SSH Key Manager, PKCS11 SSL Processor, Etc)

Better Management of Secret Sharing

Audit Log Heuristics and Analysis

Custos

Key Storage as a Service

Centralized Secret Storage

Centralized Secret Storage

Flexible Access Control

Centralized Secret Storage

Flexible Access Control

Auditing and Revocation

Making Encryption More

Usable | Flexible | Applicable


Key Storage as a Service Ecosystem

Thank You

Questions?


Extra Slides


Custos Organizational Units




Example Applications


Client-Encrypted File Locker







Multi-Device & Managed SSH Agent






Dedicated Crypto Processor







Permissions

Permission	Rights
<code>srv_grp_create</code>	create groups on a Custos server
<code>srv_grp_list</code>	list groups on a Custos server
<code>srv_grp_override</code>	escalate to any group-level permission, overriding the per-group ACS
<code>srv_audit</code>	read all server-level audit information (i.e. group creation logging, group override logging, etc)
<code>srv_clean</code>	delete all server-level audit information (i.e. group creation logging, group override logging, etc)
<code>srv_acs_get</code>	view the server-level ACS controlling the permissions in this list
<code>srv_acs_set</code>	update the server-level ACS controlling the permissions in this list

Permission	Rights
srv_grp_create	create groups on a Custos server
srv_grp_list	list groups on a Custos server

srv_	Permission	Rights
srv_	grp_obj_create	create a key:value objects within the given group
	grp_obj_list	list key:value objects within the given group
srv_	grp_obj_override	escalate to any object-level permission, overriding the per-object ACS
srv_	grp_delete	delete the given group on a Custos server
srv_	grp_audit	read all group-level audit information (i.e. object creation logging, object override logging, etc)
	grp_clean	delete all group-level audit information (i.e. object creation logging, object override logging, etc)
	grp_acs_get	view the group-level ACS controlling the permissions in this list
	grp_acs_set	update the group-level ACS controlling the permissions in this list

Permission		Rights	
srv_grp_create		create groups on a Custos server	
srv_grp_list		list groups on a Custos server	
srv_	Permission	Rights	
srv_	grp_obj_create	create a key:value objects within the given group	
	grp_obj_list	list key:value objects within the given group	
srv_	grp_	Permission	Rights
srv_	grp_	obj_delete	delete the given key:value object within the given group
srv_	grp_	obj_read	read the given key:value object within the given group
	grp_	obj_update	create a new version of the given key:value object within the given group (the equivalent of a “write” permission for the Custos write-once system)
	grp_	obj_audit	read all object-level audit information (i.e. object read logging, object update logging, etc)
	grp_	obj_clean	delete all object-level audit information (i.e. object read logging, object update logging, etc)
		obj_acs_get	view the object-level ACS controlling the permissions in this list
		obj_acs_set	update the object-level ACS controlling the permissions in this list

Access Control Chain

```
[  
  [  
    (username = 'Andy'),  
    (password = '12345'),  
    (src_ip = 192.168.1.0/24) ],  
  [  
    (username = 'Andy'),  
    (password = '12345'),  
    (src_ip = 75.148.118.216/29) ],  
  [  
    (username = 'John'),  
    (password = 'Swordfish') ]  
]
```

(username = 'Andy')

|

(password = '12345')

└──┬──

(src_ip = 192.168.1.0/24) (src_ip = 75.148.118.216/29)

(username = 'John')

|

(password = 'Swordfish')

Access Example

619a06f0-50af-11e3-8f96-0800200c9a66 ACS

```
{
  obj_read:
    [
      [ (ip\_src = '1.2.3.4'),
        (time\_utc = '1300 +/- 5') ],
      [ (user\_id = 'Dirk'),
        (psk = 'ImaHakzor') ]
      ...
    ]
    ...
}
```

Custos Server

Encryption
Key Store

Access
Control

Authentication Attributes

Source IP
Verification

Time
Verification

User ID
Verification

PSK
Verification

API

Custos API

Encrypted
File System

Dirk

Laptop



Request:

619a06f0-50af-11e3-8f96-0800200c9a66



Authentication Attributes:

user_id = Dirk

(ip_src = '1.2.3.4')

(time_utc = '1133')

Custos Server



Custos Server

Encryption
Key Store

Access
Control

Authentication Attributes

Source IP
Verification

Time
Verification

User ID
Verification

PSK
Verification

API

Custos API

Encrypted
File System



Dirk

Laptop



```
{
  obj_read:
  [
    [ (ip\_src = '1.2.3.4'),
      (time\_utc = '1300 +/- 5') ],
    [ (user\_id = 'Dirk'),
      (psk = 'ImaHakzor') ]
    ...
  ]
  ...
}
```

Custos Server



Request:

619a06f0-50af-11e3-8f96-0800200c9a66

Authentication Attributes:



user_id = Dirk

(ip_src = '1.2.3.4')

(time_utc = '1133')

```
{
  obj_read:
  [
    [ (ip\_src = '1.2.3.4'),
      (time\_utc = '1300 +/- 5') ],
    [ (user\_id = 'Dirk'),
      (psk = 'ImaHakzor') ]
    ...
  ]
  ...
}
```

Custos Server



Request:

619a06f0-50af-11e3-8f96-0800200c9a66

Authentication Attributes:

user_id = 'Dirk'

psk = 'ImaHackzor'

(ip_src = '1.2.3.4')

(time_utc = '1133')

Custos Server

Encryption
Key Store

Access
Control

Authentication Attributes

Source IP
Verification

Time
Verification

User ID
Verification

PSK
Verification

API

Custos API



Encrypted
File System

Dirk



Laptop





Custos Server



Custos Server



Custos Server



Custos Server

